

DF10

DUNIFORM®

New

General information	DF10
Article number	700080
Machine weight	13 kg
Cassette weight	0.5 kg
Electrical data	230 V AC 50 Hz 10 A
Maximum power consumption	0.7 kW
Length of cable / connection plug	2.5 m / 1 phase grounded
Press power	1200 N
Capacity	up to 8 cycles/min
Start-up heating time	15 min

Dimensions	DF10
Length	640 mm
Width	240 mm
Height	260 mm(closed) 500 mm(open)

Trays/Film/Sealing	DF10
Maximum sealable tray dimension (length x width x depth)	265 x 165 x 100 mm (>¼ GN)
Maximum film width	185 mm
Sealing temperature	Max. 200°C
Sealing technique	Manual
Number of rolls	1
MAP - Modified Atmosphere Packaging	No
Vacuum chambers	-

- Fits standard kitchen counters
- Manual sealing for easy, efficient and precise use
- Light, small and compact which makes it ideal for smaller delis
- Built of stainless steel for professional use
- Built ready for use with regular 230V
- Easy to operate and clean



Accessories for DF10

Article	Description	Benefits	Size (mm) LxWxH	Qty/ Cart.
various	Extra Cassettes DF10	-	271,5x193x16	1
102903	Spike Roll DF10	Venting	221x95x66	1

The spike roll is basically a roll with integrated sharp pins that perforate the sealing film before the tray is sealed. This device is very useful when there is a need for "breathable" packing. The sealed remains leakproof and only lets the steam come out.

