

DF25 DUNIFORM®

General information	DF25
Article number	700090
Machine weight	43 kg
Cassette weight	2.5 kg
Electrical data	230 V AC 50 Hz 10 A
Maximum power consumption	1 kW
Length of cable / connection plug	2-3 m / 1 phase grounded
Press power	1200 N
Capacity (cycles/min)	up to 10 cycles/min
Start-up heating time	20 min

Dimensions	DF25
Length	760 mm
Width	355 mm
Height	350 mm(closed) 690 mm(open)

Trays/Film/Sealing	DF25
Maximum sealable tray dimension (length x width x depth)	325 x 265 x 100 mm (¾ GN)
Maximum film width	272 mm
Sealing temperature	100°C – 180°C
Sealing technique	Semiautomatic
Number of rolls	1
MMP - Modified Atmosphere Packaging	No
Vacuum chambers	-

- Seals from sizes 1/2 GN (catering) to 1/8 GN
- Semiautomatic for precise continuous sealing
- Changeover of tray configurations in seconds
- Built of stainless steel for professional use
- Built ready for use with regular 230V
- Easy to operate and clean



Accessories for DF25

Article	Description	Benefits	Size (mm) LxWxH	Qty/ Cart.
various	Extra Cassettes DF25	from 1/2 to 1/8 GN	378x290x22	1
108824	Spike Roll DF25	Venting	320x100x68	1
	The Spike Roll is basically a roll with integrated sharp pins that perforate the sealing film before the tray is sealed. This device is very useful when there is a need for "breathable" packing. The sealed tray remains leakproof and only lets the steam come out.			
887100	Trolley Stand for DF20/25	-	900x650x670	1
103724	Trolley Stand for DF25	-	1200x650x670	1



Adapter for DF25 cassettes

